

# HANDHELD SCANNERS

**ZEBEX**  
ZEBEX INDUSTRIES INC.

\* Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.  
\* ZEBEX is the trademark of ZEBEX INDUSTRIES INC., all rights reserved.

B1F.-1, No. 207, Sec. 3, Beixin Road  
Xindian Dist, New Taipei City, Taiwan  
T. +886-2-8913 2598  
F. +886-2-8913 2596  
E. mail@zebe.com  
W. www.zebe.com

## Revel HS

### Z-3151HS Advanced Handheld High-Speed Laser Scanner

The **Revel HS** has its powerful scanning performance for up to 500 scans per second, and it guarantees an impressive, fast and accurate scanning performance.

- Decodes most popular 1D barcodes, incl. GS1 DataBar & PDF 417
- Superb scanning ability
- Proprietary Z-SCAN+ technology
- Rugged and ergonomic form factor
- Flexible communications



product  
design  
award

2009

#### OPERATIONAL

Light Source	650 nm visible laser diode (VLD)
Microprocessor	32 bit
Depth of Field	35 – 200 mm (UPC/EAN 100%, PCS=90%)
Scan Angle	52°
Scan Rate	500 scans per second
Pitch/Roll/Skew Angle	65° / 30° / 65°
Minimum Bar Width	5 mil @ PCS=90% (Code 39)
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Three-color LED (green, red & blue)
Beeper Operation	Programmable tone & beep time
System Interfaces	Keyboard, RS-232C, HID USB, wand

#### PHYSICAL

Dimensions	106.7 × 58.0 × 155.0 mm (device only)
Weight	148 g (stand excluded)
Cable	Standard 2M straight

#### POWER

Input Voltage	5 VDC ±10%
Operating Current	250 mA

#### REGULATORY

Laser Class	CDRH Class IIa; IEC 60825-1: Class 1
EMC	CE & FCC DOC compliance, VCCI, BSMI

#### ENVIRONMENTAL

Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	5% – 95% RH (non-condensing)
Light Levels	4,500 Lux (fluorescence)
Drop Durability	Designed to withstand 1M drops



 Free JavaPOS & OPOS Software  
Utilities Download Available

